



SPARES	MILL	GRIND	WIRE	EDM	F/GRIND	OTHER	REV	DATE	BY	DESCRIPTION
							A	XX-XX-XX		RELEASED FOR FULL PRODUCTION

NOTES:
 1.) RADIUS RUN OUT PERMISSIBLE AT VENT/DUMP VENT INTERSECTION.
 2.) ALL INTERNAL CORNERS R.0060" MAX UNLESS OTHERWISE NOTED.

TOLERANCES (UNLESS OTHERWISE NOTED)		MATERIAL / HARDNESS	DEALER
INCHES	MILLIMETERS		
.XX ± .01	.X ± 0.2 MM		
.XXX ± .004	.XX ± .10 MM		
.XXXX ± .0004	.XXX ± .010 MM		
.XXXXX ± .0002	.XXXX ± .005 MM		
.XX° ± .50°	.XX° ± .50°		

▶▶▶ TO EXPEDITE ASSEMBLY PROCESS ◀◀◀
 TARGET THE MIDPOINT OF ALL BIAS TOLERANCES

QUANTITY	MOLDING SURFACE FINISH	THIS DRAWING WAS PRODUCED USING	THIRD ANGLE PROJECTION	SHRINK	SHEET NUMBER
	SPE #C-1 (600 STONE)	Solid Works	DO NOT SCALE		1 of 1

SCALE	EXCEPT AS NOTED	UNITS	INCHES[mm]	REV
4:1				

Extreme COMPONENTS, LP
 EC NANO 75 ASSEMBLY